

AGB Series

Vacuum Generator

AIRBEST



Features

- ◇ Fast evacuation, high vacuum level, low air consumption
- ◇ Small size, simple structure, easy to install
- ◇ There are 3 vacuum ports with G1/8 female thread

Advantages

- ◇ High efficient and energy-saving vacuum generator, can quickly reach the max. vacuum level
- ◇ Can be used in the occasions with limited space and weight, easy to install
- ◇ Can be directly connected to suction cups to save space




Applications

- ◇ The occasions with limited installation space
- ◇ Applicable to the working conditions that require fast evacuation and low air consumption

Structure

- ◇ Housing can be freely matched with vacuum cartridges with different performance parameters
- ◇ The air supply port is directly inserted into the $\phi 4$ hose, the vacuum port is G1/8 female thread



How to order

AGB - S02-2

①

②

Series	② Specification
AGB	S02 - 2 (~75kPa) X2.5 - 2 (~90kPa) T05 - 2 (~84kPa)

◇ Note: The standard mounting accessory is type C, other types should be ordered separately if needed

Technical parameters

Model	Air supply pressure range bar	Max. vacuum level -kPa	Max. vacuum flow NL/min	Air consumption NL/min	Noise level dB(A)	Weight g	Recommended hose dia.(mm)	
							Air supply port	Vacuum port
AGB-S02-2	4.0~6.0	75	16.2	8.0	70	20	$\phi 4$	G1/8
AGB-X2.5-2	4.5~6.0	90	17.2	10.5	72	20	$\phi 4$	G1/8
AGB-T05-2	4.0~6.0	84	19.5	21.5	78	20	$\phi 4$	G1/8

