RoHS





Features

- O PU material
- Thicken the wall thickness, intermal reinforced rib structure design



- Long lifetime, excellent wear resistance, ozone resitance, oil resistance
- Effectively prevent deformation of metal sheet during handling




Applications

Handling metal sheet and aluminum plate without deformation



Structure

Split structure design, wearing parts can be replaced separately





Flat Suction Cup Special for Metal Sheet

How to order



① Series	② Diameter	③ Material & Han	rdness	 Connection thread
SDM	100 - ф100mm	U-PU	70	Nil - Suction cup only
				G2F - G1/4 female thread
				G3F - G3/8 female thread

Selection


Model	Connection thread G2F	G3F
SDM100U	SDM100U-G2F	SDM100U-G3F

Technical parameters

Model	Pull-out force N	Inner volume cm²	Min.curve radius of workpiece mm	Weight g	Recommended hose dia. mm	MPQ pcs	
SDM100	375	56	160	62	8	1	

Note: Testing vacuum level -CGSPa, workpiece with smooth and clean surface. The data of pull-out force as above are figured out without considering safety factor The data may be different according to different workpiece surfaces.

Dimensions(mm)





SDM100U-G3F SDM100U-G2F Note: The dimensional tolerance conforms to GBT3672.1-2002-1 M3 rubber product dimensional tolerance standard

Mounting parts



Item	Model	Applicable suction cup
Fitting for suction cup	PJS-G1M-SFM80	SDM100
Thread adapter	PJT-G1F-G2F	SDM100
	PJT-G1F-G3F	SDM100

PJS - Fitting for suction cup PJT - Thread adapter