

PJB Series

Universal Mounting Parts-Ball Joint

AIRBEST



Features

- Flexible connection for deflection in any direction with a maximum deflection angle of 12°
- The ball and socket are equipped with sealing rings to prevent vacuum leakage during rotation
- It is made of high strength steel and has good stability
- Suitable for large suction cup to handle workpiece with inclined surface



How to order


PJB - G4M - S

① Series	② Suction cup connection		③ External sealing device
PJB	G1M - G1/8 male thread M10M - M10×1.25 male thread	G2M - G1/4 male thread G4M - G1/2 male thread	Nil - Standard type S - With external sealing suction cup


Selection

Model/Suction cup connection		G1M	M10M	G2M	G4M
PJB-G1M	PJB-G1M-S	PJB-M10M	PJB-G2M	PJB-G4M	PJB-G4M-S

Dimensions(mm)



PJB-□



PJB-□-S

Model/Size	H	G1	L1	G2	L2	S	d	Deflection angle	Weight g
PJB-G1M	26.5	G1/8	8	G1/8	7	12	2	12°	20
PJB-M10M	37.5	G1/4	12	M10×1.25	10	19	3.5	12°	82
PJB-G2M	37.5	G1/4	12	G1/4	10	19	3.5	12°	75
PJB-G4M	40	G1/2	15	G1/2	12	24	4	12°	113

Model/Size	H	G1	L1	G2	L2	S	Deflection angle	Weight g
PJB-G1M-S	33	G1/8	8	G1/8	7	12	12°	21
PJB-G4M-S	52	G1/2	15	G1/2	12	24	12°	133