

ZPDE Series

AIRBEST

UNIVERSAL

High-precision Digital Pressure Switch

Features

- ◇ Digital display electronic pressure switch, optional two-color display
- ◇ 4-digit seven-segment LED display
- ◇ Pressure units can be converted and displayed on the screen
- ◇ Parameter values can be displayed directly on the screen

Advantages

- ◇ Monitor the system action clearly and visually, could change the setting content and backlight display mode
- ◇ The pressure is displayed on the screen, easy to read
- ◇ Easy to operate with the clear display



Application

- ◇ Monitor the vacuum system, optimize the working cycle
- ◇ Adjust the system circuit, improve economic benefit of vacuum system
- ◇ Square shape is more suitable for installing panel
- ◇ Suitable for all automation handling industries

Structure

- ◇ Electronic vacuum switch, solid polycarbonate case
- ◇ 2m connecting cable
- ◇ Optional mounting bracket and panel type mounting frame

How to order

ZPDE - C N - R1M

① ② ③ ④

① Series	② Pressure range	③ Output specification	④ Connection thread
ZPDE	C - Compound P - Positive	N - 1NPN output P - 1PNP output	R1M - Rc1/8 male thread


Selection

Model	
ZPDE-CN-R1M	ZPDE-PN-R1M
ZPDE-CP-R1M	ZPDE-PP-R1M


Technical parameters

Model		ZPDE-C (Compound)	ZPDE-P (Positive)
Rated pressure range		-100.0~100.0kPa	-0.100~1.000MPa
Setting pressure range		-103.0~103.0kPa	-0.103~1.030MPa
Withstand pressure		500kPa	1.5MPa
Fluid		Air, Non-corrosive gas/Non-flammable gas	Air, Non-corrosive gas/Non-flammable gas
Pressure unit	kPa	0.1	1
Set pressure resolution	MPa	-	-
	kgf/cm ²	0.001	0.01
	bar	0.001	0.01
	psi	0.01	0.1
	inHg	0.1	-
	mmHg	1	-
Power supply voltage		12to24V DC±10%,ripple(P-P)10% or less	
Current consumption		≤30mA (Without load)	
Switch output	Output type	Open collector (NPN) / Close collector (PNP)	
	Load current	Max.125mA	
	Residual voltage	≤1.0V	
	Response time	≤2.5ms(Chattering-proof function:25ms,100ms,250ms,500ms,1000ms,1500ms selectable)	
Display	Display	White (Sampling rate:0.2 time/sec,0.5 time/sec,1 time/sec for choice)	
	Indicator accuracy	±1%F.S.±1 digit (ambient temperature:25±3℃)	
	Repeatability	±0.3%F.S.±1 digit	
	Switch ON Indicator	White (1 indicator) OUT1	
Environment	Enclosure	IP40	
	Ambient temp. range	0~50℃	
	Temperature characteristic	±2% F.S.of rated ambient temperature 25℃ (at temp. range of 0~50℃)	
	Storage temperature	Storage:-10~60℃ (No condensation or freezing)	
	Ambient humidity	Operation/ storage:35~85%RH (No condensation)	
	Withstand voltage	1000V AC in 1-min (between case and lead wire)	
	Insulation resistance	50MΩ above (500V DC) (between case and lead wire)	
	Vibration	Total amplitude 1.5mm Or 10G,10Hz~150Hz~10Hz for 1 minute,two hours each direction of X,Y and Z	
	Shock	100m/s ² (10G)3 times each in direction of X,Y and Z	
Port size		Rc1/8, M5	
Lead wire		φ4 oil-resistance PVC cable- 3 core	
Weight		67g(with 2-meter lead wire)	

Output circuit wiring diagrams



ZPDE-□N-R1M 1NPN output




ZPDE-□P-R1M 1PNP output


Panel instructions



Dimensions (mm)



ZPDE-□N-R1M




ZPDF-A-MB Mounting bracket A type

ZPDE Series


High-precision Digital Pressure Switch

AIRBEST


Dimensions (mm)




ZPDT-B-MB Mounting bracket B type



ZPDT-PS Panel adapter



Panel type



ZPDT-PC Front protective lid + panel adapter

Accessories

Item	Model
Mounting bracket A type	ZPDT-A-MB
Mounting bracket B type	ZPDT-B-MB
Panel adapter	ZPDT-PS
Front protective lid + panel adapter	ZPDT-PC

Vacuum Accessories

ZPS

ZFA

ZFE

ZFD

ZFB

ZFL

ZFP

ZVAB

ZVAC

ZVRA

ZVEA

ZVR

ZVRH

ZVCM

ZVD

ZVT

ZVS

ZPDT

ZPDE

ZPMR

ZSA